mecc alte

Totally Focused. Totally Independent.

Technical Guide

ECP3 4 C

C-TYPE

DDS
Dynamic Data Support

The world's largest independent producer of alternators 1 – 5,000kVA

Rev. 0

Standards

Alternators are designed and produced within an ISO 9001 environment. The entire series is manufactured according to, and complies with, the most common specifications such as CEI 2-3, IEC 34-1, EN 60034-1, VDE 0530, BS 4999-5000, NF 51.111, CAN/CSA-C22.2 No14-95-No100-95, NEMA MG 1-2011, ISO 8528-3. Other standards such as UL1446, UL 1004/4 and /B are available on request.

Windings and Performances

All windings are 2/3rds pitch to eliminate triplen harmonics within the voltage waveform and to avoid excessive neutral currents in certain parallel operating conditions. A fully interconnected aluminium or copper damper cage is supplied on the rotor of all models (excluding the ECP3 series).

- 12 wire reconnectable:
  50Hz – 380V to 440V and 220/110V to 240/120V (de-rates may apply at certain voltages)
  60Hz – 380V to 480V and 220/110V to 240/120V (de-rates may apply at certain voltages)


- 6 wire reconnectable:
  50Hz – 380V to 440V and 220V to 240V (de-rates may apply at certain voltages)
  60Hz – 380V to 480V and 220V to 240V (de-rates may apply at certain voltages)

Winding Configurations	Standard		Special (dedicated)			
	12 wire Reconnectable	6 wire Reconnectable	380V and 600V 60Hz	690V 50/60Hz	220-240V 1ph 50Hz	220-240V 1ph 60Hz
ECP3 to ECO38	Std	Option	Option	Option	Option	Option
ECO40 to ECO46	Std	Option	Option	Option	Option (to ECO40)	Option (to ECO40)
Insulation materials	Class H	Class H	Class H	Class H	Class H	Class H
High efficiency	Std	Std	Std	Std	Std	Std
High motor starting	>300%	>300%	>300%	>300%	>300%	>300%
THD (Total Harmonic Distortion)	Typically <3.5% full load L-L	Typically <3.0% full load L-L	Typically <3.5% full load L-L	Typically <3.5% full load L-L	Typically <4.5% full load L-N	Typically <4.5% full load L-N
Interference suppression	VDE 0875 G/N/K, EN61000-6-3, EN61000-6-2, others available on request					

Winding Protection

There are various degrees of protection for the windings following the standard impregnation process, as can be seen here. The TOTAL+ butadienic black flexible coating is recommended for arduous applications.

Winding Protection:	STANDARD	STANDARD+	GREY	GREY+	TOTAL+ (3% de-rate may apply on certain models)
ECP3	Std	Option	Option	Option	Option
ECP28 and ECP32	-	Std	Option	Option	Option
NPE32, ECP34 to ECO46	-	-	Std	Option	Option





Grey treatment (marinization) on the left, TOTAL+ treatment shown on the right. The EG43 grey varnish, is an high temperature insulating enamel that forms a tough and flexible film, with excellent moisture and chemical protection. It is water and oil proof, and also protects windings from abrasion. It is applied spraying an over coating layer over the impregnated winding, or dipping the stator in a varnish barrel for superior treatments

The TOTAL+ is a protection system that makes Mecc Alte special. It is the ultimate winding treatment that offers truly superior performances when the environment is really harsh, or the application very demanding. It is a rubbery protection treatment, used to replace epoxies and silicones winding encapsulation. The TOTAL+ flexible black compound cures to a tough, resilient, glossy black thick coating that seals the copper against moisture and chemical attacks. Due to its encapsulation capability and flexibility, is also extremely resistant to the particle abrasion as it adsorbs the impacts. Moreover, the high flexibility leads to a long-trouble less life protection, as the compound follows elastically the thermal expansion cycles of the windings from the cold to the hot condition and vice versa without forming any cracks.

Protection for Environment

In addition to protection on the windings themselves, the alternators can have increased ingress protection. Standard levels are IP23 with further upgrades available to include inlet filters, IP43 and IP45: 7% de-rates apply on inlet filters and IP43 protection. 20-30% de-rates apply for IP45 depending on alternator model.

Additional air exit louvres (called IP23+) are optionably retrofittable in the overall ECP32 to ECO 46 range, in order to comply to the most strict marine regulations.




Construction

The robust mechanical structure withstands up to 5G in any direction and 9G vertically and its design permits easy access to the connections and components during routine maintenance check-ups. The mechanical design has used the most advanced FEM techniques. The materials used are: FEP12 steel for the frame, C45 steel for the shaft and cast iron or aluminum pressure die cast for the end-brackets: fans are aluminum die casted either nylon fiber glass loaded, UL compliant materials. Rotors are dynamically balanced according grade 2.5 of ISO 1940-1.

Terminals and Terminal Box

Easy access to regulators is assured through a pull out drawer or a drop down panel to allow safer adjustment. Large terminal boxes allow easy access of power cables, in the ECO43 and ECO46 higher power ranges the terminal allow the convenient choice of power cable or busbar connection with versatility of entry and connection. Current transformers are available as an option on series ECO 40, 43 and 46 with single or dual output.



Excitation and Regulation Systems


All ECP/ECO series have MAUX auxiliary winding to power the digital regulator. Both DSR and the DER1 are available to connect to PC through the DxR2 USB interface and DxR TERMINAL software to interrogate/download alarms & settings for analysis or for cloning other regulators. DER2 has got an integrated USB connection and can be connected to the PC without any optional connection boards. More settings such as LAMS, digital RAM based synchronous external control and soft start are obtainable through the DxR connection. Simple analogue potentiometers are available for the more usual adjustments.

Excitation Systems	DSR	DER1	DER2
ECP3 to ECO38	Std	Option	Option
ECO40 to ECO46	-	Std	Option
Parallel Operation	√	√	√
Mains Parallel	√	√	√
3 Phase Sensing (rms)	-	√	√
Accuracy	+/-1%	+/-0.5%	+/-0.5%
Remote Voltage Control	√	√	√
Alarm Log	√	√	√
Analogue and Digital Configurable	√	√	√
LAMS (Load Acceptance V/f)	√	√	√
APO (Active Protection Output)	√	√	√
Soft Start	√	√	√
High dynamic response	-	-	√
USB connection without external boards	-	-	√

For a given motor start duty a smaller machine may be selected – also enhanced by low sub-transient reactance values for non-linear loads. The whole range from 6.5 to 3400kVA is capable of >300% sustained short circuit current for up to 20 seconds.

Optional PMG3

PMG3 can be retro fit or factory fit on ECO 40, 43 and 46 series. This smart MeccAlte design allows an easy fix kit, through a tapered cone coupling and a simple replacement of the rear air louvre. PMG3 is also available on ECO 38, when ordered from the factory.



The complete AVR range is fully compatible with both MAUX and PMG3 systems, this minimises spare part management and flexibility of stock as one AVR suits all applications. The PMG3 is delivering the same amount of kVA available with the MAUX.

Accessories

Additional optionals can be fit on our alternator series, such as PTC thermistors or PT100 both on windings and bearings, space heaters, high and low profile of terminal boxes (on most series), air filter clogging sensors, rotating diode bridge failure sensor (RBD), power factor controller for parallel operation (PFR/2), parallel devices (standard from ECO 40), air filters, IP43 and IP45 protections, marine IP23 + protection for SOLAS requirements and many others.

Deration coefficients

	Ambient temperature (Celsius)					
Altitude (meters)	25	40	45	50	55	60
≤ 1000	1.07	1	0.96	0.93	0.91	0.89
> 1000 ≤ 1500	1.01	0.96	0.92	0.89	0.87	0.84
> 1500 ≤ 2000	0.96	0.91	0.87	0.84	0.83	0.79
> 2000 ≤ 3000	0.9	0.85	0.81	0.78	0.76	0.73

Notes on short circuit curves

The indicated coefficients have to be used to correct the three phase short circuit curves values as a function of the rated voltage.

50 Hz		*60 Hz*	
Voltage	*Factor*	*Voltage*	*Factor*
380	0.93X	415	0.85X
400	1X	440	0.90X
415	1.04X	460	0.95X
440	1.10X	480	1X

The indicated coefficient have to be used to correct the three phase short circuit curves values as a function of the type of short circuit voltage.

	3 phase	*2 phase L-L*	*1 phase L-N*
Istantaneous	1X	0.87X	1.30X
Minimum	1X	1.80X	3.20X
Sustained	1X	1.50X	2.50X
Max Duration	20 sec.	10 sec.	4 sec.

All the curves are shown for series or parallel star connection at 400V 50 Hz or 480V 60 Hz. If the unit is reconnected from series to parallel star, the additional coefficient is 2X. From series star to series delta, it is 1.72X. From series star to parallel delta, it is 3.44X.

General characteristics

Pole number	4	Insulation class	H
Phase number	3	Protection class	IP23
Number of wires	12	NDE Bearing type	6305-2RS
Execution	Brushless	DE Bearing type	6308-2RS
Regulator type	DSR	Maximum Overspeed	2250
Winding pitch	2/3	Altitude	0-1000
Code voltage reference	T0405S3	Balancing	ISO1940-1

Ratings 50Hz

kVA / kW @ Temp. Rise / Ambient °C - 0.8 PF

		STANDBY-163/27				STANDBY-150/40				H-125/40				F-105/40				B-80/40			
Series Star Y		380V	400V	415V	440V	380V	400V	415V	440V	380V	400V	415V	440V	380V	400V	415V	440V	380V	400V	415V	440V
Parallel Star YY		190V	200V	208V	220V	190V	200V	208V	220V	190V	200V	208V	220V	190V	200V	208V	220V	190V	200V	208V	220V
Series Delta Δ		220V	230V	240V	254V	220V	230V	240V	254V	220V	230V	240V	254V	220V	230V	240V	254V	220V	230V	240V	254V
Parallel Delta ΔΔ		110V	115V	120V	127V	110V	115V	120V	127V	110V	115V	120V	127V	110V	115V	120V	127V	110V	115V	120V	127V
ECP3 1S4 C	**kVA**	7	**7**	7	5,9	6,8	**6,8**	6,8	5,6	6,5	**6,5**	6,5	5,5	6	**6**	6	5	5,2	**5,2**	5,2	4,4
	kW	5,6	**5,6**	5,6	4,7	5,4	**5,4**	5,4	4,5	5,2	**5,2**	5,2	4,4	4,8	**4,8**	4,8	4	4,2	**4,2**	4,2	3,5
ECP3 2S4 C	**kVA**	8,8	**8,8**	8,8	7,4	8,3	**8,3**	8,3	7	8	**8**	8	6,8	7,5	**7,5**	7,5	6,4	6,4	**6,4**	6,4	5,4
	kW	7	**7**	7	5,9	6,6	**6,6**	6,6	5,6	6,4	**6,4**	6,4	5,4	6	**6**	6	5,1	5,1	**5,1**	5,1	4,3
ECP3 1L4 C	**kVA**	11,8	**11,8**	11,8	9,6	11,4	**11,4**	11,4	9,4	11	**11**	11	9	10	**10**	10	8	8,8	**8,8**	8,8	7,2
	kW	9,4	**9,4**	9,4	7,7	9,1	**9,1**	9,1	7,5	8,8	**8,8**	8,8	7,2	8	**8**	8	6,4	7	**7**	7	5,8
ECP3 2L4 C	**kVA**	14,5	**14,5**	14,5	11,8	14	**14**	14	11,4	13,5	**13,5**	13,5	11	12,5	**12,5**	12,5	10	10,8	**10,8**	10,8	8,8
	kW	11,6	**11,6**	11,6	9,4	11,2	**11,2**	11,2	9,1	10,8	**10,8**	10,8	8,8	10	**10**	10	8	8,6	**8,6**	8,6	7
ECP3 3L4 C	**kVA**	16	**16**	16	12,8	15,5	**15,5**	15,5	12,4	15	**15**	15	12	14	**14**	14	10,5	12	**12**	12	9,6
	kW	12,8	**12,8**	12,8	10,2	12,4	**12,4**	12,4	9,9	12	**12**	12	9,6	11,2	**11,2**	11,2	8,4	9,6	**9,6**	9,6	7,7

Ratings 60Hz

kVA / kW @ Temp. Rise / Ambient °C - 0.8 PF

		STANDBY-163/27				STANDBY-150/40				H-125/40				F-105/40				B-80/40			
Series Star Y		415V	440V	460V	480V	415V	440V	460V	480V	415V	440V	460V	480V	415V	440V	460V	480V	415V	440V	460V	480V
Parallel Star YY		208V	220V	230V	240V	208V	220V	230V	240V	208V	220V	230V	240V	208V	220V	230V	240V	208V	220V	230V	240V
Series Delta Δ		240V	254V	265V	277V	240V	254V	265V	277V	240V	254V	265V	277V	240V	254V	265V	277V	240V	254V	265V	277V
Parallel Delta ΔΔ		120V	127V	133V	138V	120V	127V	133V	138V	120V	127V	133V	138V	120V	127V	133V	138V	120V	127V	133V	138V
ECP3 1S4 C	**kVA**	7,5	8,4	8,4	**8,4**	7,2	8	8	**8**	7	7,8	7,8	**7,8**	6,5	7,2	7,2	**7,2**	5,6	6,2	6,2	**6,2**
	kW	6	6,7	6,7	**6,7**	5,8	6,4	6,4	**6,4**	5,6	6,2	6,2	**6,2**	5,2	5,8	5,8	**5,8**	4,5	5	5	**5**
ECP3 2S4 C	**kVA**	9,8	10,5	10,5	**10,5**	9,4	10	10	**10**	9	9,6	9,6	**9,6**	7,5	9	9	**9**	7,2	7,7	7,7	**7,7**
	kW	7,8	8,4	8,4	**8,4**	7,5	8	8	**8**	7,2	7,7	7,7	**7,7**	6	7,2	7,2	**7,2**	5,8	6,2	6,2	**6,2**
ECP3 1L4 C	**kVA**	12,9	14,3	14,3	**14,3**	12,4	13,8	13,8	**13,8**	12	13,2	13,2	**13,2**	11	12	12	**12**	9,6	10,6	10,6	**10,6**
	kW	10,3	11,4	11,8	**11,4**	9,9	11	11	**11**	9,6	10,6	10,6	**10,6**	8,8	9,6	9,6	**9,6**	7,7	8,5	8,5	**8,5**
ECP3 2L4 C	**kVA**	15,1	17,5	17,5	**17,5**	14,6	16,9	16,9	**16,9**	14	16,2	16,2	**16,2**	12,5	15	15	**15**	11,2	13	13	**13**
	kW	12,1	14	14	**14**	11,7	13,5	13,5	**13,5**	11,2	13	13	**13**	10	12	12	**12**	9	10,4	10,4	**10,4**
ECP3 3L4 C	**kVA**	17,1	19,3	19,3	**19,3**	16,7	18,8	18,8	**18,8**	16	18	18	**18**	14,5	16,5	16,5	**16,5**	12,8	14,4	14,4	**14,4**
	kW	13,7	15,4	15,4	**15,4**	13,4	15	15	**15**	12,8	14,4	14,4	**14,4**	11,6	13,2	13,2	**13,2**	10,2	11,5	11,5	**11,5**

Reactance & Time constants- Class H / 400V

Unsaturated (ref. EN60034-4)			ECP3 1S4 C	ECP3 2S4 C	ECP3 1L4 C	ECP3 2L4 C	ECP3 3L4 C
Xd	Direct-axis synchronous reactance	%	173,4	186,6	220,4	142,3	144
X'd	Direct-axis transient reactance	%	17	16,8	22	14,2	14,6
X"d	Direct-axis subtransient reactance	%	14,4	12,1	15,6	10	10
Xq	Quadrature-axis synchronous reactance	%	60,9	61,6	70,5	71	79,95
X'q	Quadrature-axis transient reactance	%	60,9	61,6	70,5	71	79,95
X"q	Quadrature-axis subtransient reactance	%	69,8	65,9	81,9	52,9	53,3
X_2	Negative-sequence reactance	%	15,9	16,6	18,8	17	17,5
X_0	Zero sequence reactance	%	6,25	5,8	6,15	5,64	5,5
Saturated							
Xd	Direct-axis synchronous reactance	%	147,4	158,6	187,3	120,9	122,4
X'd	Direct-axis transient reactance	%	14,5	14,3	18,7	12,1	12,4
X"d	Direct-axis subtransient reactance	%	12,3	10,3	13,3	8,54	8,5
Xq	Quadrature-axis synchronous reactance	%	51,7	52,4	59,9	60,4	67,96
X'q	Quadrature-axis transient reactance	%	51,7	52,4	59,9	60,4	67,96
X"q	Quadrature-axis subtransient reactance	%	59,3	56	69,6	45	45,3
X_2	Negative-sequence reactance	%	13,5	14,1	16	14,5	14,9
X_0	Zero sequence reactance	%	6,25	5,8	6,15	5,64	5,5
Kcc	Short circuit ratio		1	0,8	0,9	0,98	1,1
T'd	Transient time constant	sec	0,026	0,017	0,036	0,044	0,042
T"d	Subtransient time constant	sec	0,025	0,011	0,013	0,009	0,01
T'do	Open circuit time constant	sec	0,71	0,73	0,79	0,84	0,84
Ta	Armature time constant	sec	0,011	0,012	0,046	0,011	0,011

Additional information - Class H / 400V

Io	Excitation current at no load	A	0,36	0,29	0,34	0,35	0,35
Ic	Excitation current at full load	A	1,1	0,8	1,5	1,2	1,2
Overload			1 hour in a 6 hours period 110% rated load				
Overload per 20 sec.		%	300				
Heat dissipation		W	1157	1246	1444	1743	1905
Telephone Harmonic Factor - THF		%	<2	<2	<2	<2	<2
Waveform Distors.(THD) full load LL/LN		%	2,8 / 2,6	2,8 / 2,4	2,3 / 2	2,8 / 2,7	2,2 / 2
Waveform Distors.(THD) no load LL/LN		%	2,93 / 2,5	2,7 / 2,5	2,6 / 2,6	2,2 / 2	2,8 / 2,7

Reactance & Time constants- Class H / 480V

Unsaturated (ref. EN60034-4)			ECP3 1S4 C	ECP3 2S4 C	ECP3 1L4 C	ECP3 2L4 C	ECP3 3L4 C
Xd	Direct-axis synchronous reactance	%	173,4	186,6	220	142,3	144
X'd	Direct-axis transient reactance	%	17	16,8	22	14,2	14,6
X"d	Direct-axis subtransient reactance	%	14,4	12,1	15,6	10	10
Xq	Quadrature-axis synchronous reactance	%	60,9	61,6	70,5	71	79,95
X'q	Quadrature-axis transient reactance	%	60,9	61,6	70,5	71	79,95
X"q	Quadrature-axis subtransient reactance	%	69,8	65,9	81,9	52,9	53,3
X_2	Negative-sequence reactance	%	15,9	16,6	18,8	17	17,5
X_0	Zero sequence reactance	%	6,25	5,8	6,15	5,64	5,5
Saturated							
Xd	Direct-axis synchronous reactance	%	147,4	158,6	187	120,9	122,4
X'd	Direct-axis transient reactance	%	14,5	14,3	18,7	12,1	12,4
X"d	Direct-axis subtransient reactance	%	12,3	10,3	13,3	8,54	8,5
Xq	Quadrature-axis synchronous reactance	%	51,7	52,4	59,9	60,4	67,96
X'q	Quadrature-axis transient reactance	%	51,7	52,4	59,9	60,4	67,96
X"q	Quadrature-axis subtransient reactance	%	59,3	56	69,6	45	45,3
X_2	Negative-sequence reactance	%	13,5	14,1	16	14,5	14,9
X_0	Zero sequence reactance	%	6,25	5,8	6,15	5,64	5,5
Kcc	Short circuit ratio		1	0,8	0,9	0,98	1,1
T'd	Transient time constant	sec	0,026	0,017	0,036	0,044	0,042
T"d	Subtransient time constant	sec	0,025	0,011	0,013	0,009	0,01
T'do	Open circuit time constant	sec	0,71	0,73	0,79	0,84	0,84
Ta	Armature time constant	sec	0,011	0,012	0,046	0,011	0,011


Additional information - Class H / 480V

Io	Excitation current at no load	A	0,25	0,27	0,3	0,32	0,32
Ic	Excitation current at full load	A	1,0	0,8	1,4	1,2	1,2
Overload			1 hour in a 6 hours period 110% rated load				
Overload per 20 sec.		%	300				
Heat dissipation		W	1251	1314	1481	1784	1927
Telephone Interferance Factor - TIF			<45	<45	<45	<45	<45
Waveform Distors.(THD) full load LL/LN		%	2,8 / 2,6	2,8 / 2,4	2,3 / 2	2,8 / 2,7	2,2 / 2
Waveform Distors.(THD) no load LL/LN		%	2,93 / 2,5	2,7 / 2,5	2,6 / 2,6	2,2 / 2	2,8 / 2,7


Efficiencies @ 50Hz

Models		380V 50Hz					400V 50Hz					415V 50Hz					440V 50Hz				
		0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1
ECP3 1S4 C	%	75,1	78,8	82,1	81,7	81,4	75,0	78,9	82,4	81,8	81,5	74,8	78,9	82,3	81,5	81,0	74,3	78,6	82,0	81,3	80,9
ECP3 2S4 C	%	75,5	80,3	84,4	83,6	83,3	75,6	80,4	84,7	83,7	83,4	75,4	80,4	84,6	83,4	82,9	74,9	80,1	84,3	83,2	82,8
ECP3 1L4 C	%	81,1	84,3	86,1	85,8	85,5	81,0	84,4	86,4	85,9	85,4	80,8	84,4	86,3	85,6	85,0	80,3	84,1	86,0	85,4	84,8
ECP3 2L4 C	%	82,0	85,0	86,4	86,0	85,7	82,0	85,1	86,7	86,1	85,6	81,8	85,1	86,6	85,8	85,2	81,3	84,8	86,3	85,6	85,0
ECP3 3L4 C	%	81,8	85,3	86,6	86,2	85,9	81,8	85,4	86,9	86,3	85,8	81,6	85,4	86,8	86,0	85,4	81,1	85,1	86,5	85,8	85,2


ECP3 1S4 C
400/230 50Hz




ECP3 2S4 C
400/230 50Hz




ECP3 1L4 C
400/230 50Hz



ECP3 2L4 C
400/230 50Hz




ECP3 3L4 C
400/230 50Hz




Efficiencies @ 60Hz

Models		415V 60Hz					440V 60Hz					460V 60Hz					480V 60Hz				
		0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1
ECP3 1S4 C	%	76,2	80,1	83,3	82,6	82,1	76,0	80,2	83,5	83,1	82,8	76,1	80,3	83,7	83,2	82,9	76,4	80,4	83,9	83,3	82,9
ECP3 2S4 C	%	76,8	81,6	85,7	84,7	84,2	76,6	81,7	85,9	85,2	84,9	76,7	81,8	86,1	85,3	84,9	77,0	81,9	86,3	85,4	85,0
ECP3 1L4 C	%	81,8	85,1	87,2	87,0	86,5	81,6	85,2	87,4	87,5	87,1	81,7	85,3	87,6	87,6	87,1	82,0	85,4	87,8	87,7	87,1
ECP3 2L4 C	%	82,8	85,8	87,4	87,2	86,7	82,6	85,9	87,6	87,7	87,3	82,7	86,0	87,8	87,8	87,4	83,0	86,1	88,0	87,9	87,3
ECP3 3L4 C	%	82,6	86,1	87,8	87,5	87,0	82,4	86,2	88,0	88,0	87,6	82,5	86,3	88,2	88,1	87,7	82,8	86,4	88,4	88,2	87,6


ECP3 1S4 C
480/277 60Hz




ECP3 2S4 C
480/277 60Hz




ECP3 1L4 C
480/277 60Hz



ECP3 2L4 C
480/277 60Hz




ECP3 3L4 C
480/277 60Hz



Transients voltage


400V - 50Hz

Motor Starting @ P.F. 0,6




480V - 60Hz


Motor Starting @ P.F. 0,6




Phase Loading @ P.F. 0,8




Phase Loading @ P.F. 0,8



Load Shedding @ P.F. 0,8



Load Shedding @ P.F. 0,8




In order to scale transient curves as a function of a power factor or voltage if not indicated, please proceed as follows:

Power Factor coefficient corrector (PFCC), to be used on power factor 0.6 curves:
PFCC=sin(ARCcos (PFnew))/0.8
Example. The PFCC at power factor 0.3 is 1.192 [PFCC= sin(ARCcos (0.3))/0.8]. This means that the voltage fall at a given power at pf 0.3 is equivalent to the one that can be read on the pf 0.6 curve if the load is considered 1.192 times bigger (19% higher value.).
In this example, a 100 kVA load insertion at pf 0.3 is equivalent in voltage fall to a 119kVA load insertion at pf 0.6.


Voltage coefficient corrector (VCC):
VCC=(400/Vnew)2 if 50 Hz; VCC=(480/Vnew)2 if 60 Hz
Example. VCC at 415V 60 Hz is 1.338 [VCC=(480/415)^2]. This means that the voltage fall at a given power at 415V is equivalent to the one that can be read on the power factor 0.6 curve if the load is considered 1.338 times bigger (33% higher value.).
In this example, a 100 kVA load insertion at 415V is equivalent in voltage fall to a 133kVA load insertion at 480V.

50Hz Short circuit decrement curves - No load excitation at rated speed


ECP3 1S4 C




ECP3 2S4 C



ECP3 1L4 C




ECP3 2L4 C



*Please refer to tables at page 6

50Hz Short circuit decrement curves - No load excitation at rated speed


ECP3 3L4 C




*Please refer to tables at page 6

60Hz Short circuit decrement curves - No load excitation at rated speed


ECP3 1S4 C




ECP3 2S4 C



ECP3 1L4 C




ECP3 2L4 C



*Please refer to tables at page 6

60Hz Short circuit decrement curves - No load excitation at rated speed

ECP3 3L4 C




*Please refer to tables at page 6

Additional Characteristics


Data		ECP3 1S4 C		ECP3 2S4 C		ECP3 1L4 C		ECP3 2L4 C		ECP3 3L4 C	
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz
Damper cage		None									
Stator Winding Resistance (20°C)	Ω	0,969		0,636		0,457		0,366		0,314	
Rotor Winding Resistance (20°C)	Ω	6,078		7,141		8,539		9,743		10,884	
Stator Exciter Resistance (20°C)	Ω	15,71		15,71		15,71		15,71		15,71	
Rotor Exciter Resistance (20°C)	Ω	1,453		1,453		1,453		1,453		1,453	
Weight of complete generator	kg	59,0		65,0		79,0		87,0		93,0	
Unbalanced magnetic pull	kN/mm	2,5		2,8		2,9		3,0		3,0	
Air flow	m^3/min	3,5	3,9	3,5	4,1	3,3	4,0	3,0	3,5	3,0	3,5
Noise level at 1m/7m	dB(A)	72/58	78/60	72/58	78/60	72/58	78/60	72/58	78/60	72/58	78/60

PQ Diagram




ECP3 1S4 C

TWO BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.41	0.00207
2	MAIN ROTOR	12.32	0.03773
3	EX. ROTOR	4.34	0.01118
4	SHAFT	4.45	0.00091
TOTAL		21.52	0.05189

TWO BEARING DIMENSIONS




C.G.= GRAVITY CENTER

1)	COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2)	PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE *REMOVABLE PANEL FOR ACCESS TO AVR*
3)	PRE-TAGLIO PER INGRESSO CAVI Ø28mm *PRE-CUT FOR CABLE ENTRY Ø28mm*
4)	VITE M4 PER MESSA A TERRA *SCREW M4 FOR GROUNDING*

ECP3 1S4 C


SINGLE BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.39	0.00206
2	MAIN ROTOR	12.32	0.03773
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.02	0.00121
TOTAL		22.07	0.05218

SAE N°	5 SHAFTS COUPLING FLEX PLATE A	B	WEIGHT [kg]	J [kg m²]
6 1/2	3	1.5	0.97	0.00496
7 1/2	3	1.5	1.18	0.00770
8	34.6	29.5	1.76	0.01114
10	26.6	23.4	2.14	0.02220
11 1/2	13	10.8	2.59	0.03512

SINGLE BEARING DIMENSIONS



SAE N.	GIUNTI A DISCHI / DISC COUPLING / DISCQUE DE MONOPALIER / SCHEIBENKUPPLUNG d	L	Q1	N1	S1	α1
6 1/2	215.9	30.2	200	6	9	60°
7 1/2	241.3	30.2	222.25	8	9	45°
8	263.52	62	244.47	6	11	60°
10	314.32	53.8	295.27	8	11	45°
11 1/2	352.42	39.6	333.37	8	11	45°


SAE N.	FLANGIA / FLANGE / BRIDE / FLANSCH O	P	Q	S	N	α
6	308	266.7	285.75	11	8	45°
5	356	314.3	333.4	11	8	45°
4	403	362	381	11	12	30°
3	451	409.6	428.6	11	12	30°

C.G.= GRAVITY CENTER

1) COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI / *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2) PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE / *REMOVABLE PANEL FOR ACCESS TO AVR*
3) PRE-TAGLIO PER INGRESSO CAVI Ø28mm / *PRE-CUT FOR CABLE ENTRY Ø28mm*
4) VITE M4 PER MESSA A TERRA / *SCREW M4 FOR GROUNDING*
5) CENTRO DI GRAVITA' IN CONFIGURAZIONE SAE 5 VOLANO 7.5 / *GRAVITY CENTER IN CONFIGURATION SAE 5 FLYWHEEL 7.5*


ECP3 2S4 C

TWO BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.41	0.00207
2	MAIN ROTOR	14.56	0.04441
3	EX. ROTOR	4.34	0.01118
4	SHAFT	4.45	0.00091
TOTAL		23.76	0.05857

TWO BEARING DIMENSIONS




C.G.= GRAVITY CENTER

1)	COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2)	PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE *REMOVABLE PANEL FOR ACCESS TO AVR*
3)	PRE-TAGLIO PER INGRESSO CAVI Ø28mm *PRE-CUT FOR CABLE ENTRY Ø28mm*
4)	VITE M4 PER MESSA A TERRA *SCREW M4 FOR GROUNDING*

ECP3 2S4 C


SINGLE BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.39	0.00206
2	MAIN ROTOR	14.56	0.04441
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.02	0.00121
TOTAL		24.31	0.05886

SAE N°	5 SHAFTS COUPLING FLEX PLATE A	B	WEIGHT [kg]	J [kg m²]
6 1/2	3	1.5	0.97	0.00496
7 1/2	3	1.5	1.18	0.00770
8	34.6	29.5	1.76	0.01114
10	26.6	23.4	2.14	0.02220
11 1/2	13	10.8	2.59	0.03512

SINGLE BEARING DIMENSIONS



SAE N.	GIUNTI A DISCHI / DISC COUPLING / DISCQUE DE MONOPALIER / SCHEIBENKUPPLUNG d	L	Q1	N1	S1	α1
6 1/2	215.9	30.2	200	6	9	60°
7 1/2	241.3	30.2	222.25	8	9	45°
8	263.52	62	244.47	6	11	60°
10	314.32	53.8	295.27	8	11	45°
11 1/2	352.42	39.6	333.37	8	11	45°


SAE N.	FLANGIA / FLANGE / BRIDE / FLANSCH O	P	Q	S	N	α
6	308	266.7	285.75	11	8	45°
5	356	314.3	333.4	11	8	45°
4	403	362	381	11	12	30°
3	451	409.6	428.6	11	12	30°

C.G.= GRAVITY CENTER

1) COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI / *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2) PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE / *REMOVABLE PANEL FOR ACCESS TO AVR*
3) PRE-TAGLIO PER INGRESSO CAVI Ø28mm / *PRE-CUT FOR CABLE ENTRY Ø28mm*
4) VITE M4 PER MESSA A TERRA / *SCREW M4 FOR GROUNDING*
5) CENTRO DI GRAVITA' IN CONFIGURAZIONE SAE 5 VOLANO 7.5 / *GRAVITY CENTER IN CONFIGURATION SAE 5 FLYWHEEL 7.5*


ECP3 1L4 C

TWO BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.41	0.00207
2	MAIN ROTOR	18.69	0.05687
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.17	0.00107
TOTAL		28.61	0.07119


TWO BEARING DIMENSIONS



1)	COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2)	PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE *REMOVABLE PANEL FOR ACCESS TO AVR*
3)	PRE-TAGLIO PER INGRESSO CAVI Ø28mm *PRE-CUT FOR CABLE ENTRY Ø28mm*
4)	VITE M4 PER MESSA A TERRA *SCREW M4 FOR GROUNDING*

ECP3 1L4 C


SINGLE BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.39	0.00206
2	MAIN ROTOR	18.69	0.05687
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.73	0.00136
TOTAL		29.15	0.07147

SAE N°	5 SHAFTS COUPLING FLEX PLATE			
	A	B	WEIGHT [kg]	J [kg m²]
6 1/2	3	1.5	0.97	0.00496
7 1/2	3	1.5	1.18	0.00770
8	34.6	29.5	1.76	0.01114
10	26.6	23.4	2.14	0.02220
11 1/2	13	10.8	2.59	0.03512

SINGLE BEARING DIMENSIONS



SAE N.	GIUNTI A DISCHI / DISC COUPLING DISCQUE DE MONOPALIER / SCHEIBENKUPPLUNG					
	d	L	Q1	N1	S1	α1
6 1/2	215.9	30.2	200	6	9	60°
7 1/2	241.3	30.2	222.25	8	9	45°
8	263.52	62	244.47	6	11	60°
10	314.32	53.8	295.27	8	11	45°
11 1/2	352.42	39.6	333.37	8	11	45°


SAE N.	FLANGIA / FLANGE BRIDE / FLANSCH					
	O	P	Q	S	N	α
6	308	266.7	285.75	11	8	45°
5	356	314.3	333.4	11	8	45°
4	403	362	381	11	12	30°
3	451	409.6	428.6	11	12	30°

C.G.= GRAVITY CENTER

1) COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI
REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS
2) PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE
REMOVABLE PANEL FOR ACCESS TO AVR
3) PRE-TAGLIO PER INGRESSO CAVI Φ28mm
PRE-CUT FOR CABLE ENTRY Φ28mm
4) VITE M4 PER MESSA A TERRA
SCREW M4 FOR GROUNDING
5) CENTRO DI GRAVITA' IN CONFIGURAZIONE SAE 5 VOLANO 7.5
GRAVITY CENTER IN CONFIGURATION SAE 5 FLYWHEEL 7.5


ECP3 2L4 C

TWO BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.41	0.00207
2	MAIN ROTOR	22.47	0.06834
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.17	0.00107
TOTAL		32.39	0.08266

TWO BEARING DIMENSIONS




C.G.= GRAVITY CENTER

1)	COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2)	PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE *REMOVABLE PANEL FOR ACCESS TO AVR*
3)	PRE-TAGLIO PER INGRESSO CAVI Ø28mm *PRE-CUT FOR CABLE ENTRY Ø28mm*
4)	VITE M4 PER MESSA A TERRA *SCREW M4 FOR GROUNDING*

ECP3 2L4 C


SINGLE BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.39	0.00206
2	MAIN ROTOR	22.47	0.06834
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.73	0.00136
TOTAL		32.93	0.08294

SAE N°	5 SHAFTS COUPLING FLEX PLATE			
	A	B	WEIGHT [kg]	J [kg m²]
6 1/2	3	1.5	0.97	0.00496
7 1/2	3	1.5	1.18	0.00770
8	34.6	29.5	1.76	0.01114
10	26.6	23.4	2.14	0.02220
11 1/2	13	10.8	2.59	0.03512

SINGLE BEARING DIMENSIONS



SAE N.	GIUNTI A DISCHI / DISC COUPLING DISCQUE DE MONOPALIER / SCHEIBENKUPPLUNG					
	d	L	Q1	N1	S1	α1
6 1/2	215.9	30.2	200	6	9	60°
7 1/2	241.3	30.2	222.25	8	9	45°
8	263.52	62	244.47	6	11	60°
10	314.32	53.8	295.27	8	11	45°
11 1/2	352.42	39.6	333.37	8	11	45°


SAE N.	FLANGIA / FLANGE BRIDE / FLANSCH					
	O	P	Q	S	N	α
6	308	266.7	285.75	11	8	45°
5	356	314.3	333.4	11	8	45°
4	403	362	381	11	12	30°
3	451	409.6	428.6	11	12	30°

C.G.= GRAVITY CENTER

1) COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI
REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS
2) PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE
REMOVABLE PANEL FOR ACCESS TO AVR
3) PRE-TAGLIO PER INGRESSO CAVI Φ28mm
PRE-CUT FOR CABLE ENTRY Φ28mm
4) VITE M4 PER MESSA A TERRA
SCREW M4 FOR GROUNDING
5) CENTRO DI GRAVITA' IN CONFIGURAZIONE SAE 5 VOLANO 7.5
GRAVITY CENTER IN CONFIGURATION SAE 5 FLYWHEEL 7.5


ECP3 3L4 C

TWO BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.41	0.00207
2	MAIN ROTOR	24.46	0.07433
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.17	0.00107
TOTAL		34.38	0.08865

TWO BEARING DIMENSIONS




C.G.= GRAVITY CENTER

1)	COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI *REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS*
2)	PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE *REMOVABLE PANEL FOR ACCESS TO AVR*
3)	PRE-TAGLIO PER INGRESSO CAVI Ø28mm *PRE-CUT FOR CABLE ENTRY Ø28mm*
4)	VITE M4 PER MESSA A TERRA *SCREW M4 FOR GROUNDING*

ECP3 3L4 C


SINGLE BEARING MOMENTS OF INERTIA



POS.	COMPONENT	WEIGHT [kg]	J [kg m²]
1	FAN	0.39	0.00206
2	MAIN ROTOR	24.46	0.07433
3	EX. ROTOR	4.34	0.01118
4	SHAFT	5.73	0.00136
TOTAL		34.92	0.08893

SAE N°	5 SHAFTS COUPLING FLEX PLATE			
	A	B	WEIGHT [kg]	J [kg m²]
6 1/2	3	1.5	0.97	0.00496
7 1/2	3	1.5	1.18	0.00770
8	34.6	29.5	1.76	0.01114
10	26.6	23.4	2.14	0.02220
11 1/2	13	10.8	2.59	0.03512

SINGLE BEARING DIMENSIONS



SAE N.	GIUNTI A DISCHI / DISC COUPLING DISCQUE DE MONOPALIER / SCHEIBENKUPPLUNG					
	d	*L*	*Q1*	*N1*	*S1*	*α1*
6 1/2	215.9	30.2	200	6	9	60°
7 1/2	241.3	30.2	222.25	8	9	45°
8	263.52	62	244.47	6	11	60°
10	314.32	53.8	295.27	8	11	45°
11 1/2	352.42	39.6	333.37	8	11	45°

SAE N.	FLANGIA / FLANGE BRIDE / FLANSCH					
	O	*P*	*Q*	*S*	*N*	*α*
6	308	266.7	285.75	11	8	45°
5	356	314.3	333.4	11	8	45°
4	403	362	381	11	12	30°
3	451	409.6	428.6	11	12	30°

C.G.= GRAVITY CENTER

1) COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI
REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS
2) PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE
REMOVABLE PANEL FOR ACCESS TO AVR
3) PRE-TAGLIO PER INGRESSO CAVI Φ28mm
PRE-CUT FOR CABLE ENTRY Φ28mm
4) VITE M4 PER MESSA A TERRA
SCREW M4 FOR GROUNDING
5) CENTRO DI GRAVITA' IN CONFIGURAZIONE SAE 5 VOLANO 7.5
GRAVITY CENTER IN CONFIGURATION SAE 5 FLYWHEEL 7.5

Notes

Mecc Alte SpA (HQ)
Via Roma
20 – 36051 Creazzo
Vicenza – ITALY
T: +39 0444 396111
F: +39 0444 396166
E: info@meccalte.it
aftersales@meccalte.it

Mecc Alte Portable
Via Roma
20 – 36051 Creazzo
Vicenza – ITALY
T: +39 0444 396111
F: +39 0444 396166
E: info@meccalte.it
aftersales@meccalte.it

Mecc Alte Power Products srl
Via Melaro
2 – 36075 Montecchio
Maggiore (VI) – ITALY
T: +39 0444 1831295
F: +39 0444 1831306
E: info@meccalte.it
aftersales@meccalte.it

Zanardi Alternatori srl
Via Dei Laghi
48/B – 36077 Altavilla
Vicenza – ITALY
T: +39 0444 370799
F: +39 0444 370330
E: info@zanardialternatori.it

United Kingdom
Mecc Alte U.K. LTD
6 Lands' End Way
Oakham
Rutland LE15 6RF
T: +44 (0) 1572 771160
F: +44 (0) 1572 771161
E: info@meccalte.co.uk
aftersales@meccalte.co.uk

Spain
Mecc Alte España S.A.
C/ Rio Taibilla, 2
Polig. Ind. Los Valeros
03178 Benijofar (Alicante)
T: +34 (0) 96 6702152
F: +34 (0) 96 6700103
E: info@meccalte.es
aftersales@meccalte.es

China
Mecc Alte Alternator Haimen LTD
755 Nanhai East Rd
Jiangsu HEDZ 226100 PRC
T: +86 (0) 513 82325758
F: +86 (0) 513 82325768
E: info@meccalte.cn
aftersales@meccalte.cn

India
Mecc Alte India PVT LTD
Plot NO: 1, Sanaswadi
Talegaon
Dhamdhere Road Taluka:
Shirur. District:
Pune - 412208
Maharashtra, India
T: +91 2137 619600
F: +91 2137 619699
E: info@meccalte.in
aftersales@meccalte.in

U.S.A. and Canada
Mecc Alte Inc.
1229 Adams Drive
McHenry, IL, 60051
T: +1 815 344 0530
F: +1 815 344 0535
E: info@meccalte.us
aftersales@meccalte.us

Germany
Mecc Alte Generatoren GmbH
Ensener Weg 21
D-51149 Köln
T: +49 (0) 2203 503810
F: +49 (0) 2203 503796
E: info@meccalte.de
aftersales@meccalte.de

Australia
Mecc Alte Alternators PTY LTD
10 Duncan Road, PO Box 1046
Dry Creek, 5094, South
Australia
T: +61 (0) 8 8349 8422
F: +61 (0) 8 8349 8455
E: info@meccalte.com.au
aftersales@meccalte.com.au

France
Mecc Alte International S.A.
Z.E.La Gagnerie
16330 ST.Amant de Boixe
T: +33 (0) 545 397562
F: +33 (0) 545 398820
E: info@meccalte.fr
aftersales@meccalte.fr

Far East
Mecc Alte (F.E.) PTE LTD
19 Kian Teck Drive
Singapore 628836
T: +65 62 657122
F: +65 62 653991
E: info@meccalte.com.sg
aftersales@meccalte.com.sg

mecc alte

www.meccalte.com