

SC27G900D2

Used for 650kVA generator



◎ POWER RATING

Engine Speed	Type of	Engine Power	
rpm	Operation	kW	Ps
1500	Prime Power	602	819
	Standby Power	662	900

-. The engine performance is as per GB/T2820.

-. Ratings are based on GB/T1147.1.

---Prime power is available for an unlimited number of hours per year in a variable load application. The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

---Standby power is available in the event of a utility power outage or under test conditions for up to 200 hours of operation per year.

The permissible average power output over 24 hours of operation shall not exceed 80% of the standby power rating.

◎ SPECIFICATIONS

◎ FUEL CONSUMPTION

○ Engine Model	SC27G900D2	○ Power	lit/hr
○ Engine Type	V-type,4 strokes, water-cooled	25%	39.9
	Turbo charged	50%	73.1
	air-to-air intercooled	75%	108.4
○ Combustion type	Direct injection	100%	145.6
○ Cylinder Type	Wet liner	110%	162.4
○ Number of cylinders	12		
○ Bore × stroke	135(5.32) × 155(6.1) mm(in.)		
○ Displacement	26.6(1623) lit.(in3)		
○ Compression ratio	16 : 1		

○ Firing order 1-12-5-8-3-10-6-7-2-11-4-9

◎ FUEL SYSTEM

○ Injection timing	13±0.5°BTDC	○ Injection pump	Yijie in-line “P” type
○ Dry weight	Approx. 2080kg (4586 lb)	○ Governor	Electric type
○ Dimension	1930×1686×1872mm	○ Feed pump	Mechanical type
(L×W×H)	(76×66.4×73.8 in.)	○ Injection nozzle	Multi hole type
○ Rotation	Counter clockwise viewed from	○ Opening pressure	240kg/cm2 (3414 psi)
	Flywheel	○ Fuel filter	Full flow, cartridge type

○ Fly wheel housing	SAE NO.0	○ Used fuel	Diesel fuel oil
○ Fly wheel	SAE NO.18		
◎ MECHANISM		◎ LUBRICATION SYSTEM	
○ Type	Over head valve	○ Lub. Method	Fully forced pressure feed type
○ Number of valve	Intake 1, exhaust 1 per cylinder	○ Oil pump	Gear type driven by crankshaft
○ Valve lashes at cold	Intake 0.325mm (0.0128 in.)	○ Oil filter	Full flow, cartridge type
	Exhaust 0.375mm (0.0148 in.)	○ Oil pan capacity	High level 65 liters (17.16 gal.) Low level 55 liters (14.52 gal.)
◎ VALVE TIMING		○ Angularity limit	Front down 25 deg. Front up 35 deg.
	Opening		Close
○ Intake valve	20 deg. BTDC		48 deg. ABDC
○ Exhaust valve	48 deg. BBDC		20 deg. ATDC
◎ COOLING SYSTEM		○ Lub. Oil	Refer to Operation Manual
◎ ENGINEERING DATA			
○ Cooling method	Fresh water forced circulation	○ Water flow	740 liters/min @1,500 rpm
○ Water capacity	48L (12.7 gal.)	○ Heat rejection to coolant	60.5kcal/sec /1500 rpm
(engine only)		○ Heat rejection to CAC	37.8kcal/sec /1500 rpm
○ Pressure system	Max. 0.5 kg/cm ² (7.11 psi)	○ Air flow	2×25.5m ³ /min /1500 rpm
○ Water pump	Centrifugal type driven by belt	○ Exhaust gas flow	2×62.2m ³ /min /1500 rpm
○ Water pump Capacity	740 liters (195.36 gal.)/min	○ Exhaust gas temp.	650 °C @1,500 rpm
	at 1,500 rpm (engine)	○ Max. permissible	
○ Thermostat	Wax–pellet type	restrictions	
	Opening temp. 77°C	Intake system	3 kPa initial 6 kPa final
	Full open temp. 90°C		
○ Cooling fan	Blower type,iron	Exhaust system	6 kPa max.
	1220 mm diameter, 6 blades	○ Max. permissible altitude	2,000 m
○ Cooling air flow	18.024 m ³ /s	○ Fan power	25 kW

◎
 ELECTRICAL SYSTEM

○ Charging generator	28V×55A
○ Voltage regulator	Built-in type IC regulator
○ Starting motor	24V×11kW
○ Battery Voltage	24V
○ Battery Capacity	200 AH

◆
 CONVERSION TABLE

in. = mm × 0.0394	lb/ft = N.m × 0.737
PS = kW × 1.3596	U.S. gal = lit. × 0.264
psi = kg/cm2 × 14.2233	kW = 0.2388 kcal/s
in ³ = lit. × 61.02	lb/PS.h = g/kW.h × 0.00162
hp = PS × 0.98635	cfm = m3/min × 35.336
lb = kg × 2.20462	

