

# Model: DGS-44S Powered by SDEC

POWER	PRIME	STANDBY
KVA	40	44
KW	32	35

GENSET SPECIFICATIONS			
ENGINE	4ZT3.2-G11		
Voltage (V)	380/220		
Phase	3		
Frequency (Hz)	50		
RPM (rpm)	1500		
Power factor	0.8		
Fuel Consumption (I/h)			
· <b>110</b> %	11.2		
· <b>100</b> %	10.1		
· <b>75</b> %	7.6		



DIMENSIONS AND WEIGHT				
Dimensions (LxWxH) (mm)	≤ 2100x900x1305			
Weight (kg)	≤ 850			
Noise level @ 7m	≤ 75 ∓ 5dB			
Fuel tank	Option			

#### Remarks:

- 1. All specifications in this catalog are subject to change withour prior notice for product improvement purposes.
- 2. All images shown are for illustrative purpose only.
- 3. Final weight and dimensions will depend on completed specification.
- \* Standard reference condition:: air inlet temperature 27°C, altitude 100m (328ft) A.S.L. 30% relative humidity
- \* **Sound proof canopy:** Every Digenso genset canopy is designed to simplify asembling process, protect the machine and maintain acceptable noise level. Canopy is assembled directly with stands and fuel tank inside, made by structured steels, surface covered with electricity insulated paint, ensure the quality of machine even while running at harshest environment.
  - 1. Prime power: ISO 8528 prime power is the maximum power available during a variable power sequence, which maybe run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.
  - 2. Standby power: It is defined as the maximum power available, under the agreed operating conditions, for which the generating set capable of delivering for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.





#### **ENGINE: SDEC** 4ZT3.2-G11

GENSET SPECIFICATIONS				
Governor Type				
Cylinders Number	4			
Displacement (I)	3.2			
Compression Ratio	18:1			
Cooler type	Water cooling, fan and radiator			
Aspiration				
Bore x Stroke (mm)	98 x 105			
Engine's weight (kg)	285			

# **ALTERNATOR**

GENSET SPECIFICATIONS	
No of bearings	1
Pole	4 pole, brushless
Connection type	Star
Insulation class	Class H
Voltage regulator	A.V.R
Voltage regulation	<b>∓ 1%</b>
Excitation system	Self-excited
Protection rating	IP23
Alternator's weight(kg)	165





### CONTROLLER: DSE 6020 (Made in U.K)

## **MEASUREMENTS**

- · Mains & genset voltages
- Mains & genset frequency
- Mains & genset phase currents
- Main & genset power (kVA kW kVAr)
- Power factor Cos φ
- · Hours-counter
- Battery voltage
- Engine speed r.p.m.

#### COMMANDS AND OTHERS

- Four operation modes: OFF Manual starting Automatic starting Automatic test
- · Pushbutton for forcing Mains contactor or Genset contactor
- Push-buttons: start/stop, fault reset, up/down/page/enter selection
- · Remote starting and stopping availability
- · DC system disconnection switch
- · Acoustic alarm
- · Automatic battery charger
- Fully configurable via PC using USB, RS232 & RS485 communication
- Settable PASSWORD for protection level

# **PROTECTIONS**

- Engine protections: low fuel level, low oil pressure, high engine temperature
- Genset protections: under/over voltage, overload, under/over frequency, starting failure, under/over battery voltage, battery charger failure
- Over current protection
- Independent earth fault protection

CONTROLLER OPTIONS							
DEEPSEA 6120	DEEPSEA 7320	DEEPSEA 8620	ComAp AMF20	ComAp IL9	Sices GC315		
U.K	U.K	U.K	Czech	Czech	Italy		

